

Standard Smart Battery Charger

CH3000

Moltech Power Systems

Model	CH3000i	110V N. American 3-pin connector + 220V European 2-pin connector + 240V UK 3-pin connector + 220V Australia/China connector	
	CH3000A	110V N. American 3-pin connector	
Weight	220g (not including external PSU)		
Dimensions	58mm x 180mm x 92mm		
Mating Connector	Tyco (AMP) style 5 way standard male battery connector		
LED Status	Green	Flashing	Charging in Progress
		Solid	Charging Completed
	Red	Solid	Error
Power Supply	90-260VAC 24V, 1.5A Wall mounted PSU (UL Listed, CE Compliant)		
LiIon Batteries	NI2020, NC2040, NI2040, NF2040, NL2020, NL2024, ND2017, NL2044		
NiMH Batteries	NI1030, NJ1020		



CH3000 shown with
NI2020 (not included)

- Fully compatible with Inspired Energy Standard Smart Batteries
- Unique Design
- Charge function
- Fully compatible SMBus communications
- Conforms to the Smart Battery Charger Specifications
- 5 Blade industry standard connector

The content of this information sheet does not constitute a warranty. Contact your Moltech Sales Representative for latest technical and safety information.
Copyright © Moltech Power Systems Ltd, 2005. All rights reserved. Document reference CH3000LS Issue 3, 11/2005

Moltech Power Systems Ltd

Unit 20 Loomer Road, Chesterton, Newcastle-under-Lyme,
Staffordshire, United Kingdom, ST5 7LB

Tel +44 (0) 1782 566688, Fax +44 (0) 1782 565910,

Email: sales@moltechpower.co.uk Website: www.moltechpower.co.uk

